

E HSS Cobalt slotted countersink hole type

in Schafrichtung abgeführt und können die Sen-

Range of application:

Countersink and deburring tool with through hole which is ideal for long chip materials, such as aluminium and very effective on both hard and softwoods. Spoil is removed through centre of cutter to prevent damage to tool.




Wear-resistant



Precise



HSS Co5 **90°**



Oberfläche: blank
Surface: bright
Superficie: brillante



Twistpack with tag

Größe Size / Tamaño	d1 mm	d2 mm	Bereich / Range Intervalo Ø mm	Code 2291 Art.-Nr.	Cont.
1	10,00	6	2-5	0229101000100	1
2	14,00	8	5-10	0229101400100	1
3	21,00	10	10-15	0229102100100	1
4	28,00	12	15-20	0229102800100	1
5	35,00	15	20-25	0229103500100	1

HSS Cobalt Querlochsensersatz BOX 3



3-tlg. / 3-pcs. / 3-unid.

Kunststoffbox / Plastic box / Caja de plástico

Art.-Nr. 0229100003100

Ø mm	Stk. ⁽¹⁾ pc. ⁽¹⁾
HSS Cobalt	
Ø 10,00 / 14,00 / 21,00	1

⁽¹⁾

Pieces each dimension



Taps, dies, countersinks and conecut