



**Screw-in sleeve, M6 internal thread**



- > For Ø 7.5 mm hole
- > With SW6 hexagon socket head
- > Galvanized zinc alloy

Length	Cat. No.	Order Qty
13 mm	030.01.000	100
20 mm	030.02.266	100

**Screw-in sleeve, M8 internal thread**




- > For Ø 11 mm hole
- > With SW8 hexagon socket head and rim
- > Dynafix inserts
- > Bright zinc-plated die cast zinc alloy

Length	Cat. No.	Order Qty
13 mm	030.02.182	100

**T-Nut**



Galvanized finish



- > With 4 prongs
- > Steel
- > Order qty: Multiples of 100 pcs

Internal thread	External Ø	Sleeve Ø	Rim thickness	Length	Cat. No.
Bright					
M4	Ø 15 mm	Ø 5 mm	0.8 mm	7 mm	031.00.249
M5	Ø 17 mm	Ø 6.3 mm	1 mm	7 mm	031.00.258
M6	Ø 19 mm	Ø 7.4 mm	1.1 mm	7.8 mm	031.00.267
M8	Ø 22 mm	Ø 9.2 mm	1.2 mm	9.8 mm	031.00.285
M10	Ø 25 mm	Ø 11.3 mm	1.3 mm	11 mm	031.00.301
Galvanized					
M4	Ø 15 mm	Ø 5 mm	0.8 mm	7 mm	031.00.445
M5	Ø 17 mm	Ø 6.3 mm	1 mm	7 mm	031.00.446
M6	Ø 19 mm	Ø 7.4 mm	1.1 mm	7.8 mm	031.00.463
M8	Ø 22 mm	Ø 9.2 mm	1.2 mm	9.8 mm	031.00.481



> Please order screw-in sleeves, T-nuts and allen keys in multiples of order quantity shown

**Hex key**



- > Galvanized steel

Size	Cat. No.	Order Qty
SW 3	008.28.230	100
SW 4	008.28.044	100
SW 5	008.28.250	100
SW 6	008.28.260	100

**Hex key**



- > Galvanized steel

Size	Cat. No.	Order Qty
SW 8	008.28.089	100
SW 10	008.28.100	100