



Varianta screw, countersunk head



- > For Ø 5 mm hole
- > Nickel-plated steel

Length	Driver required	Cat. No.	Order Qty
10.5 mm	PZ2	013.04.712	100


Varianta screw, countersunk head



- > For Ø 5 mm hole
- > Nickel-plated steel

Length	Driver required	Cat. No.	Order Qty
10.5 mm	PZ2	013.01.711	100


Varianta screw, countersunk head



- > For Ø 5 mm hole
- > Steel

Length	Driver required	Cat. No.	Order Qty
Nickel-plated			
10.5 mm	PZ2	013.05.719	100
13.5 mm	PZ2	340.29.724	100
16.0 mm	PZ2	013.15.733	100
Galvanized			
10.5 mm	PZ2	013.15.915	100


Varianta screw, countersunk head



- > For Ø 5 mm hole
- > Nickel-plated steel

Length	Driver required	Cat. No.	Order Qty
10.5 mm	PZ2	013.15.715	100
13.5 mm	PZ2	013.15.724	100


Varianta screw, countersunk head



- > For Ø 5 mm holes
- > Galvanized steel

Length	PZ2 driver	TS 20 driver	Order Qty
8.0 mm	013.14.908	013.40.908	1000
10.5 mm	013.14.910	013.40.910	1000
16.0 mm	013.14.930	013.40.920	1000
25.0 mm	013.14.950	-	1000


Varianta screw, raised head



- > For Ø 5 mm hole
- > Steel

Length	Driver required	Cat. No.	Order qty
Nickel-plated			
10.5 mm	PZ2	264.25.794	100
13.5 mm	PZ2	264.25.785	100
Galvanized			
10.5 mm	PZ2	264.25.990	100


Varianta screw, cylinder head



- > For Ø 5 mm hole
- > Steel

Length	Driver required	Cat. No.	Order Qty
Nickel-plated			
16.0 mm	PZ2	013.20.743	100
Galvanized			
16.0 mm	PZ2	013.20.949	100

Varianta screw, cylinder head



- > For Ø 5 mm hole
- > Nickel-plated steel

Length	Driver required	Cat. No.	Order Qty
10.5 mm	PZ2	013.08.710	100 pcs

DRAWER SYSTEMS, STAYS AND HINGES 2015, © Häfele U.K. Ltd 2015. Dimensional data not binding. We reserve the right to alter specifications without notice.