


## HÄFELE 110° SMUSO QUICK FIXING SOFT CLOSE HINGES

9

Furniture Hinges and Flap Fittings: Hinges




Drilling dimensions for cup fixing  
Drilling pattern 45/9.5



- > Opening angle 110°
- > Full overlay, half overlay/twin or inset mounting
- > Automatic closing
- > Ø 35 mm cup
- > For door thickness 14-26 mm see table below
- > Side adjustment  $\pm 3$  mm, height adjustment  $\pm 2$  mm (via mounting plate), depth adjustment  $\pm 2$  mm
- > Screw fixing cup
- > Smuso - with integrated soft closing mechanism
- > Quick fixing arms
- > Drilling pattern 45/9.5
- > Integrated soft close
- > Nickel-plated pressed steel cup and arm
- > Order fixing screws separately for screw fixing versions
- > Order qty: 1 pc

## Full overlay mounting



Overlay - coverage of the side end by door e mm

| 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 |   |
|----|----|----|----|----|----|----|----|----|---|
|    |    |    |    | 3  | 4  | 5  | 6  | 7  | 0 |
|    |    | 3  | 4  | 5  | 6  | 7  |    |    | 2 |
| 3  | 4  | 5  | 6  | 7  |    |    |    |    | 4 |

DBE distance to cup bore edge mm      Mounting plate height f mm



smuso



Drilling pattern

45/9.5

Screw fixing

311.04.000

Approved by Product Info. Dept.

PAGE AMENDED  
02.05.19/1