



Building & DIY Products You Can Trust

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: info@everbuild.co.uk

website: www.everbuild.co.uk

CONSTRUCTION PRODUCTS REGULATION

DECLARATION OF PERFORMANCE

No: 703/1-CPR/ 2013

| | |
|------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| 1. Identification Code | Everbuild 702 Water Resistant Tile Adhesive CODES: FIX005, FIX01, FIX02, FIX05, FIX10 |
| 2. Type, Batch and/or Serial Number | - For batch number - see packaging |
| 3. Intended use | Improved dispersion adhesive with reduced slip for internal tiling |
| 4. Manufacturer | Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW ,UK |
| 5. Authorised Representative | Not Applicable |
| 6. Assessment and Verification of Constancy of Performance | System 3 |
| 7. Notified Body and Tasks | CERAM UK - Initial Type testing Notified Body Ref; 1289 Test report ref; 604022881 |
| 8. European Technical Assessment | Not Applicable |
| 9. Declared Performance | EN 12004: 2007 +A1 2012 - D2T |
| Classification | D2T |
| Reaction to fire | Class E |
| Release of dangerous substances | See MSDS |
| Initial shear adhesion strength | ≥1N/mm² |



Site 41, Knowsthorpe Way,
Cross Green Industrial Estate, Leeds, LS9 0SW
Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424
Fax: +44 (0) 113 240 0024
e-mail: info@everbuild.co.uk
website: www.everbuild.co.uk

| | |
|-----------------------------------------------|-------------------------|
| Shear strength after heat aging | $\geq 1\text{N/mm}^2$ |
| Open time tensile adhesion strength (20 mins) | $\geq 0.5\text{N/mm}^2$ |
| Adhesion strength after water immersion | $\geq 0.5\text{N/mm}^2$ |
| Adhesive strength at elevated temperatures | $\geq 1.0\text{N/mm}^2$ |
| Reduced Slip | $\leq 0.5\text{mm}$ |
| Notified body reference | 1289 |

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9 . The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed: I. G. Southerington - Technical Manager

Dated: Leeds, 1/7/2013