

Quick Dry

Rustins

Chopping Board Oil

Anti-Bacterial

Ideal for
Chopping
boards
Wooden
worktops
Butcher
blocks



HEALTH AND SAFETY

Causes skin irritation.
Causes serious eye
irritation.

Keep out of reach
of children.

Wash hands, forearms
and face thoroughly after
handling. IF ON SKIN:

Wash with plenty of water.

IF IN EYES: Rinse cautiously
with water for several minutes. Remove contact
lenses, if present and easy to do. Continue
rinsing. If skin irritation occurs: Get medical
advice/attention. If eye irritation persists: Get
medical advice/attention.

UFI: RC5A-7FUJ-SW00-RFDT

Please refer to Product Data Sheet for full
information at www.rustins.co.uk



EU Limit value for this product
(CAT A/h): 30g/l (2010).

This product contains
max 3 g/l VOC.

For information on Rustins' products visit our
website at www.rustins.co.uk or contact us at
Rustins Ltd, Waterloo Road, London, NW2 7TX
United Kingdom rustins@rustins.co.uk
Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade,
Dublin D13 Y860 Ireland.

Tel: +353 1 - 832 3300

250ml e



WARNING

SHAKE WELL BEFORE USE

Rustins Chopping Board Oil is a blend of natural plant oils to nourish and protect chopping boards and worktops. It penetrates the wood with no surface film to chip. It has a clear finish to enhance the natural beauty of wood.

The Oil contains anti-microbial additives with a slow release formula which provide protection against a wide range of bacteria.

Rustins Chopping Board Oil conforms to The Articles in Contact with Food Regulations.

Preparation

The surface must be clean and bare.
Sand smooth if necessary.

Application

Do not dilute product. With a clean soft
cloth or brush apply a liberal coat of the
oil, working with the grain. Wipe off
any excess oil within 3-5 minutes. Oil
new or bare wood 3 times initially.

Re-Coating Time

Chopping Board Oil is touch dry within
one hour and can generally be re-
coated within 3 hours.

Maintenance

When applying to previously oiled wood
surfaces, first clean and remove any
contamination with warm water and
mild detergent. Re-oil weekly or
monthly with one coat depending on
use. You may lightly sand the wood
with a fine grade of sand paper to
ensure surface is smooth prior to re-
coating. For compatibility on previously
oiled wood, try a small test area first.

Coverage

1 litre covers approximately 12 square
metres per coat depending on the
absorbency of the wood.

Cleaning

Remove as much oil as possible from
brushes before cleaning. Clean brushes
whilst wet with water and detergent.

Important

Rags used for oiling must be laid out
flat to dry or destroyed, otherwise they
may catch fire due to spontaneous
combustion.

Disposal (pollution prevention)

Some local authorities have special
facilities for disposal of waste
paints/varnishes/ coatings. Do not
empty product into drains or
watercourses.

Storage

Store in a cool dry place with the lid
tightly closed. Protect from frost.

