

SHAKE WELL BEFORE USE

Rustins Exterior Wood Oil is a unique water-borne blend of natural plant oils and other special ingredients to nourish and protect all types of outdoor timber. The oil dries with a low lustre finish. The plant oils originate from sustainable sources and are used largely to replace crude oil derived components used in synthetic resins.

It is a penetrating oil drying to a hard durable and water resistant seal that brings out the beauty of the grain within the timber. It enhances the warmth and depth to hard and soft woods. It contains ultra violet light inhibitors to protect against sunlight.

If applied correctly, the oil will not leave a surface film to peel off.

Rustins Exterior Wood Oil conforms to The Articles in Contact with Food Regulations.

Preparation

The surface must be clean, sanded smooth and free from contaminants like wax and dirt. For best results apply to dry, sound wood with a moisture content between 12-20%. Do not apply to green timber. Oily woods (e.g. Teak, Iroko) should be cleaned thoroughly with white spirit before application of Rustins Exterior Wood Oil. Oak and softwoods are prone to weather staining caused by moisture activating mould spores present naturally in the wood. It is advisable to treat the wood with Rustins Advanced Clear Wood Preserver before applying Rustins Exterior Wood Oil. Bare wood may be dyed if required with Rustins Wood Dye. If a natural open grain is not required such as with oak, then use Rustins Grain Filler prior to oiling.

Application

Do not dilute the product. Using a clean soft cloth or brush apply a liberal coat of Rustins Exterior Wood Oil, working with the grain. Wipe off any excess within 3-5 minutes. New or bare wood needs to be oiled 3 times initially. Some wood may need a light sanding between coats.

Re-Coating Time

Rustins Exterior Wood Oil is touch dry within 1 hour, and can be recoated within 3 hours depending on temperature and humidity.

Do not use below 10°C, in damp conditions or if rain is imminent.

Maintenance

Regular maintenance is recommended to keep surfaces in good condition. When applying to previously oiled wood the surface should be first cleaned and any wax removed with white spirit or Rustins Surface Cleaner. If compatibility with a previously coated surface is not known, then test by applying to a small area first.

Coverage

1 litre covers approximately 13 square metres per coat depending on the absorbency of the wood.

Cleaning

Remove as much product as possible from brushes before cleaning. Clean brushes whilst wet with water and detergent. Hard brushes can be cleaned with Rustins Brush Restorer.

Important

Rags used for oiling must be laid out flat to dry or destroyed, otherwise they may catch fire.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes/coatings. Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with lid tightly closed. Protect from frost.

HEALTH AND SAFETY:

Contains othillone (ISO); 2-octyl-2H-isothiazol-3-one. May produce an allergic reaction. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

Keep out of reach of children.

Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands, forearms and face thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective clothing, eye protection, face protection. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

UFI: 7S57-90SF-T005-Y4AV

Please refer to Product Data Sheet for full information at www.rustins.co.uk



EU Limit value for this product (CAT A/h): 30g/l (2010). This product contains max 3g/l VOC.

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom rustins@rustins.co.uk

Telephone: +44 (0)20 8450 4666
ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300

Rustins

EST 1924



Made in UK

Rustins

EST 1924

Quick Dry

Exterior Wood Oil

Easy wipe-on,
natural finish



Rustins

EST 1924

Ideal for

Tables

Chairs


Loungers

Benches

Window
Frames/Sills

Gates

Solid Wood
Doors



1 Litre e

HIGH UV PROTECTION FOR EXTERIOR WOOD