

Rustins

High Heat Black Paint

Ideal for wood burning stoves & BBQs

Heat resistant up to 600°C



Matt Finish



STIR WELL BEFORE USE
and ensure any sediment is mixed-in.

Rustins High Heat Black Paint is a fast-drying protective and decorative paint which is stable to temperatures of 600°C. It is suitable for use on ferrous metals such as wood burning stoves, barbeques, domestic and industrial stoves, furnace chimneys, grates and exhausts.

Preparation

The surface must be clean, dry and free from grease, dust, rust and other contaminants. Remove all rust with a scraper or use Rustins Rust Remover. Suitable for use on bare metal. If using over previously coated surface, test a small area for compatibility.

Application

Stir well before use until there is no sediment on the bottom of the tin. Apply with a bristle paint brush. One light coat will be enough to cover most surfaces. Do not apply a second coat.

Spray Application: The paint can be sprayed with a conventional spray gun at approximately 60 lbs per square inch and also by airless spray method. Clean spray guns with Rustins Brush Cleaner.

Important: Do not apply the product at temperatures below 5°C or at a relative humidity above 90%.

Drying Time

The surface will be touch dry within 15 minutes and can be handled in 1 hour in good conditions. The painted article if air dried will become fully cured once it has been heated up to between 200 – 220°C for approximately 20 minutes. Care should be taken with the paint film until this has occurred.

Coverage

1 litre covers approximately 15 square metres per coat depending on the type of application equipment and method of application.

Cleaning

Remove excess product from brushes before cleaning whilst wet with Rustins Xylene Thinners or Rustins Cellulose Thinners. Hard brushes can be cleaned with Rustins Brush Restorer.

Maintenance

Re-application can be carried out when required to keep surfaces in good condition. Clean the surface first with white spirit and ensure that it is clean, dry and free from grease.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with the lid tightly closed. Do not expose to heat, sparks or open flame. The shelf life of the product is 2 years. The product can be used after the shelf life has expired but should first be checked to ensure it has not deteriorated in quality.

HEALTH AND SAFETY
Flammable liquid and vapour.

Causes skin irritation.
Harmful to aquatic life with long lasting effects.

Take precautionary measures against static discharge.

Wash hands thoroughly after handling.

Avoid release to the environment.

Wear eye protection.

IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

In case of fire: Use carbon dioxide for extinction.

Please refer to Product Data Sheet for full information at www.rustins.co.uk

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom
rustins@rustins.co.uk

Telephone: +44 (0)20 8450 4666



Warning



EU Limit for this product (CatA/I):
500g/l (2010).
This product contains max 499g/l (VOC).



500ml