LOW ODOUR

CLEAN BRUSHES WITH WATER

CAN ALSO BE USED ON HARDBOARD & WOOD

> UNSEALED MDF

PAINT ON UNSEALED MDF

SEALED

PAINT ON SEALED M D F





STIR WELL BEFORE USE

Rustins MDF clear sealer is formulated with a water based acrylic emulsion which has a milky-white appearance whilst liquid but dries to a clear sealer. When dry it can be painted or varnished with solvent or water based products.

Preparation

The surface must be clean and free from wax and grease.

Application

Stir before use and apply liberally and evenly with a synthetic fibre brush, pad or sponge. If finishing with a gloss paint, edges and rebated or routed areas may require a second application of sealer. For best results, apply an undercoat after sealing and before applying final gloss

Re-coating Time

The sealer will be touch dry in approximately 30 minutes depending upon the temperature and humidity and can be re-coated after a minimum of two hours.

Coverage

This tin will cover approximately 30 sq m per coat.

Cleaning

Remove as much sealer as possible and return to this container. Brushes should then be cleaned immediately with water. It the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings.

Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

HEALTH AND SAFETY

Contains a mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one [ec no 247-500-7] and 2-methyl-2h-isothiazol-3-o. May produce an allergic reaction. Keep out of reach of children. Do not get in eyes, on skin, or on clothing. IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell. IF ON SKIN: Gently wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention.

Please refer to Product Data Sheet for full information at www.rustins.co.uk

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom rustins@rustins.co.uk

Telephone: +44 (0)20 8450 4666



EU Limit value for this product (CAT A/d): 30g/l (2010)
This product contains max 16 g/l VOC



2.5Litree