




Rustins

One Coat Damp Seal

Can be applied to damp surfaces

Re-decorate in a day

Allows trapped moisture to escape



Fast drying

Seals & blocks damp stains

Re-coatable in 2 hours

Seals & blocks damp stains

STIR WELL BEFORE USE

Rustins Damp Seal is a fast drying high performance interior paint which permanently covers damp, water stains and most household stains. It dries with a long lasting permanent seal over damp walls and ceilings and can be over coated with gloss or emulsion paint as well as wall paper. It does not cure the damp but is specially formulated to allow trapped moisture to escape over time so preventing flaking of the paint or peeling of wallpaper. It is not suitable for use outdoors.

Preparation

The surface must be clean and free from dust and any loose paint, fungal growth or solid matter likely to interfere with the penetration of the sealer. Repair any damage to the surface first and sand smooth rough areas. Rustins Damp Seal should not be applied to saturated walls or newly plastered surfaces. These should be allowed to dry out for one week before application of the seal. Sources of damp should be eliminated before treatment.

Application

Stir well before use. If necessary, use Rustins Xylene Thinners to thin the Damp Seal. Apply by brush over the affected area and apply 30 cms beyond the affected area. One coat is sufficient but 2 coats will provide improved durability. Allow 2 hours before commencing painting and decorating. Cold damp conditions will significantly extend the drying times.

Re-coating Time

The primer will be touch dry in approximately 30 minutes depending on temperature and humidity

and can be re-coated with a further coat of primer or top coat after a minimum of two hours.

Coverage

1 litre will cover approximately 7 sq.m in 1 coat depending on the absorbency of the surface.

Cleaning

Remove as much product as possible from the brush or other application equipment prior to cleaning. Clean brushes and equipment immediately after use by washing in Rustins Xylene Thinners or Rustins Brush Cleaner. Hard brushes can be cleaned using Rustins Brush Restorer. Do not empty product into drains or water courses.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

HEALTH AND SAFETY

Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. Suspected of damaging the unborn child. May cause damage to organs (kidneys) through prolonged or repeated exposure (inhalation/ vapour). Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical equipment. Do not breathe vapours. Wear protective gloves. IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse.



Warning

Please refer to Product Data Sheet for full information at www.rustins.co.uk

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom rustins@rustins.co.uk Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



EU limit value for this product (cat AII): 500g/l (2010). This product contains max 495g/l VOC



500ml e