



STIR WELL BEFORE USE

Rustins Quick Drying White Primer & Undercoat is for use on indoor and outdoor work. Used as a primer, it is suitable for new and bare wood, MDF, plaster, brickwork and cement. It has high opacity and can be used as an undercoat on primed or painted surfaces. This paint may be over-coated with water or solvent based finishing paints. A Grey Primer & Undercoat is also available.

Preparation

When used as a primer, the surface must be clean and free from wax and grease. Wood must be sanded smooth and knots sealed with Rustins Knotting. For use as an undercoat on previously painted surfaces, clean and lightly sand to provide a key. Fill all holes and cracks with Rustins Wood Stopping after priming.

Application

Stir well before use and apply quickly and evenly with brush or roller. Use brushes with synthetic fibres, manufactured for use with water-based products. **PRIMING:** For application by brush, if necessary the priming coat can be thinned with up to one part of water to five parts of paint. **UNDERCOATING:** Prepare surface as above. Do not thin. Apply quickly and evenly with brush or roller.

Re-coating Time

Surface dry 30 minutes. Re-coatable after a minimum of 2 hours depending on temperature and humidity.

Coverage

1 litre covers approximately 13 square metres depending on the condition of the surface to which the paint is applied.

Cleaning

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

HEALTH AND SAFETY


Contains texanol, a mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one [ec no 247-500-7] and 2-methyl-2h-isothiazol-3-o. May produce an allergic reaction. May cause an allergic skin reaction. Keep out of reach of children. Do not get in eyes, on skin, or on clothing. Wear protective gloves and eye protection. IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If removing paint that is over ten years old, it may contain lead. Do not use sandpaper to remove, as it will create harmful dust. Use Rustins Strypt Paint & Varnish Strippier.



Warning



EU Limit value for this product (CAT A/d): 130g/l (2010)
This product contains max 110g/l VOC



500ml e

Please refer to Product Data Sheet for full information at www.rustins.co.uk

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom rustins@rustins.co.uk
Telephone: +44 (0)20 8450 4666

**RECOATABLE
IN 2 HOURS**

LOW ODOUR

**EXCELLENT
OPACITY**

**SAFE FOR
CHILDREN'S
TOYS**

**CLEAN
BRUSHES
IN WATER**

Rustins

**QUICK DRYING
PRIMER AND
UNDERCOAT**



PRIMER

Does both jobs!

WHITE



UNDERCOAT

BARE WOOD

**1 COAT
WOOD PRIMER**

**SECOND COAT
UNDERCOAT**