

Rustins

POLYURETHANE Varnish

EXTRA TOUGH POLYURETHANE FOR INTERIOR USE

Enhances the beauty of wood
Resists alcohol & boiling water

For use on:
Window Ledges
Tables & Chairs
Doors
Shelving
Cupboards
Bannisters

SATIN
CLEAR



STIR WELL BEFORE USE

A tough and durable varnish that can be used on bare wood, hardboard, MDF and unsealed cork.

Preparation

The surface must be clean, smooth, dry and free from wax, dust and contaminants. For best results, previously varnished surfaces should be stripped with Rustins Strypit Paint and Varnish Stripper. If not stripping, the surface should be rubbed down with glasspaper or wet and dry paper. Remove any wax by rubbing with White Spirit and steel wool and wipe away whilst wet. Cracks may be filled with Rustins Wood Filler. Open grained wood can be filled with Rustins Grainfiller.

Application

Stir well before use or it will dry to a gloss finish. **Important.** Coloured varnish will darken with additional coats. Using a good quality brush, apply evenly. Avoid brushing too vigorously, as this will cause air bubbles to form. The first coat can be thinned with white spirit, typically 10%, to improve penetration. If used over a solvent-based wood dye apply the first coat with a minimum of brushing.

Re-coating Time

Further coats can be applied once the previous coat is dry. This will be between 2-8 hours depending on the temperature and humidity at the time of application. Bare wood will require 2-3 coats. Sand lightly between coats if necessary.

Coverage

1 litre will cover approximately 12-14 sq.m in 1 coat depending on the absorbency of the surface.

Cleaning

Remove excess product from brushes before cleaning whilst wet with white spirit or Rustins Brush Cleaner. Hard brushes can be cleaned with Rustins Brush Restorer.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with the lid tightly closed.



HEALTH & SAFETY

Flammable liquid and vapour. May cause drowsiness or dizziness. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapour/spray.



Warning

Use only outdoors or in a well-ventilated area. Ensure maximum ventilation during application and drying.

Wear protective gloves/ protective clothing/ eye protection/ face protection.
IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.

Store in a well-ventilated place. Keep container tightly closed.

Contains HYDROCARBONS, C9 - C11. n-alkanes, isoalkanes,cyclics,<2% aromatics.

UFI: C9GV-JOUC-W31S-8P9G

Please refer to Product Data Sheet for full information at www.rustins.co.uk

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom rustins@rustins.co.uk Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300

PLEASE NOTE: COLOUR ILLUSTRATED ON FRONT IS AS NEAR AS THE PRINTING PROCESS PERMITS.



EU Limit value for this product (CAT A/E):
400g/l (2010)
This product contains max 396 g/l VOC

500ml e



Rustins

POLYURETHANE Varnish

EXTRA TOUGH POLYURETHANE FOR INTERIOR USE

Enhances the beauty of wood
Resists alcohol & boiling water

For use on:
Window Ledges
Tables & Chairs
Doors
Shelving
Cupboards
Bannisters

GLOSS
CLEAR



STIR WELL BEFORE USE

A tough and durable varnish that can be used on bare wood, hardboard, MDF and unsealed cork.

Preparation

The surface must be clean, smooth, dry and free from wax, dust and contaminants. For best results, previously varnished surfaces should be stripped with Rustins Strypit Paint and Varnish Stripper. If not stripping, the surface should be rubbed down with glasspaper or wet and dry paper. Remove any wax by rubbing with White Spirit and steel wool and wipe away whilst wet. Cracks may be filled with Rustins Wood Filler. Open grained wood can be filled with Rustins Grainfiller.

Application

Stir well before.

Important. Coloured varnish will darken with additional coats. Using a good quality brush, apply evenly. Avoid brushing too vigorously, as this will cause air bubbles to form. The first coat can be thinned with white spirit, typically 10%, to improve penetration. If used over a solvent-based wood dye apply the first coat with a minimum of brushing.

Re-coating Time

Further coats can be applied once the previous coat is dry. This will be between 2-8 hours depending on the temperature and humidity at the time of application. Bare wood will require 2-3 coats. Sand lightly between coats if necessary.

Coverage

1 litre will cover approximately 12-14 sq.m in 1 coat depending on the absorbency of the surface.

Cleaning

Remove excess product from brushes before cleaning whilst wet with white spirit or Rustins Brush Cleaner. Hard brushes can be cleaned with Rustins Brush Restorer.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with the lid tightly closed.



HEALTH & SAFETY

Flammable liquid and vapour. May cause drowsiness or dizziness. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapour/spray.



Warning

Use only outdoors or in a well-ventilated area. Ensure maximum ventilation during application and drying.

Wear protective gloves/ protective clothing/ eye protection/ face protection.
IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.

Store in a well-ventilated place. Keep container tightly closed.

Contains HYDROCARBONS, C9 - C11. n-alkanes, isoalkanes, cyclics, <2% aromatics.

UFI: C9GV-JOUC-W31S-8P9G

Please refer to Product Data Sheet for full information at www.rustins.co.uk

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom rustins@rustins.co.uk Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300

PLEASE NOTE: COLOUR ILLUSTRATED ON FRONT IS AS NEAR AS THE PRINTING PROCESS PERMITS.



EU Limit value for this product (CAT A/e):
400g/l (2010)
This product contains max 396 g/l VOC

500ml e



Rustins

POLYURETHANE Varnish

EXTRA TOUGH POLYURETHANE FOR INTERIOR USE

Enhances the beauty of wood
Resists alcohol & boiling water

For use on:
Window Ledges
Tables & Chairs
Doors
Shelving
Cupboards
Bannisters

MATT
CLEAR



Coverage

1 litre will cover approximately 12-14 sq.m in 1 coat depending on the absorbency of the surface.

Cleaning

Remove excess product from brushes before cleaning whilst wet with white spirit or Rustins Brush Cleaner. Hard brushes can be cleaned with Rustins Brush Restorer.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with the lid tightly closed.



HEALTH & SAFETY

Flammable liquid and vapour. May cause drowsiness or dizziness. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapour/spray.



Warning

Use only outdoors or in a well-ventilated area. Ensure maximum ventilation during application and drying.

STIR WELL BEFORE USE

A tough and durable varnish that can be used on bare wood, hardboard, MDF and unsealed cork.

Preparation

The surface must be clean, smooth, dry and free from wax, dust and contaminants. For best results, previously varnished surfaces should be stripped with Rustins Strypit Paint and Varnish Stripper. If not stripping, the surface should be rubbed down with glasspaper or wet and dry paper. Remove any wax by rubbing with White Spirit and steel wool and wipe away whilst wet. Cracks may be filled with Rustins Wood Filler. Open grained wood can be filled with Rustins Grainfiller.

Application

Stir well before use or it will dry to a gloss finish. **Important.** Coloured varnish will darken with additional coats. Using a good quality brush, apply evenly. Avoid brushing too vigorously, as this will cause air bubbles to form. The first coat can be thinned with white spirit, typically 10%, to improve penetration. If used over a solvent-based wood dye apply the first coat with a minimum of brushing.

Re-coating Time

Further coats can be applied once the previous coat is dry. This will be between 2-8 hours depending on the temperature and humidity at the time of application. Bare wood will require 2-3 coats. Sand lightly between coats if necessary.

Wear protective gloves/ protective clothing/ eye protection/ face protection.
IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.

Store in a well-ventilated place. Keep container tightly closed.

Contains HYDROCARBONS, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics, HYDROCARBONS C9 AROMATICS
UFI: C9GV-JOUC-W31S-8P9G

Please refer to Product Data Sheet for full information at www.rustins.co.uk

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom rustins@rustins.co.uk
Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300

PLEASE NOTE: COLOUR ILLUSTRATED ON FRONT IS AS NEAR AS THE PRINTING PROCESS PERMITS.



EU Limit value for this product (CAT A/e):
400g/l (2010)
This product contains max 396 g/l VOC

500ml e

