

Rustins

Wood Dye is available in
13 attractive wood shades

Pine

Light Oak

Ebony

Antique Pine

Medium Oak

Light Teak

Dark Teak

Red Mahogany

Dark Oak

Brown Mahogany

Walnut

Quick Dry White

Quick Dry Grey

Please note these colours
are as near as the printing
process permits

Rustins

WOOD DYE

FOR INTERIOR & EXTERIOR



Ideal for floors

*Penetrating stain for all
new or stripped wood*

*Will not raise the grain
Easy to apply*

Rustins

Ideal for:

Floors

**Indoor & outdoor
furniture**

**Staircases
& bannisters**

Doors

Cupboards

Worktops

**Skirting boards
& architraves**

**Picture
frames**



250mle

STIR WELL BEFORE USE

Quick drying penetrating stain for all new or stripped wood. Easy to apply and will not raise the grain. For use on bare wood prior to finishing with any of Rustins' wood finishes. Suitable for interior and exterior use.

Preparation

The surface must be clean, smooth, dry and dust free. Any existing coating must be removed before the application, preferably with a paint remover such as Rustins Stripit Paint & Varnish Stripper. The best method is to sand the area, but if it has been waxed at any time, it is essential that the wax and any other contamination is removed using Rustins Grade 3 Steel Wool and white spirit. Wipe off the solution of wax formed with a clean rag and allow to dry before sanding. If the wax is not removed, sanding may force the wax further into the wood causing adhesion and drying problems. Any imperfections in the wood can be filled with Rustins Professional Woodfiller. If purchasing more than one container to dye a large area, mix the contents together in a larger container before use to ensure that there is no variation in shade. It is advisable to test for compatibility on a small area before proceeding.

The dye can only be used on bare wood.

Application

Stir well before and during use until there is no sediment on the bottom of the tin. Apply evenly with a clean dry cloth in a warm dry atmosphere. On soft absorbent wood a second coat may be applied. Hard woods should only be given one coat. If more are applied the extra coats may not penetrate and will rub off. Where a lighter shade is required, the dye may be diluted with white spirit. Dilution must not exceed 2 parts dye to 1 part white spirit. All colours can be inter-mixed to make other shades.

Re-Coating Time

The wood dye will be touch dry in approximately 6-8 hours depending upon the temperature and humidity and can be re-coated after a minimum of eight hours.

Coverage

1 litre will cover approximately 24 sq m per coat depending on the absorbency of the wood.

Cleaning

Remove excess product from brushes before cleaning whilst wet with white spirit or Rustins Brush Cleaner. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes/coatings. Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with lid tightly closed. Protect from frost.

HEALTH AND SAFETY

Contains Hydrocarbons, C9 - C11, n alkanes, isooalkanes, cyclics, <2% aromatics; Hydrocarbons, C9, aromatics. Repeated exposure may cause skin dryness or cracking. Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective clothing, eye protection, face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Dispose of contents and container to hazardous or special waste collection point. In accordance with local, regional, national and/or international regulation.

UFI: C058-M7EX-REDT-C2K1

Please refer to Product Data Sheet for full information at www.rustins.co.uk

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Watford Road, London, NW2 7TX United Kingdom
rustins@rustins.co.uk
Telephone: +44 (0)20 8450 4666
RDI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



DANGER