

Worktop Oil is a unique water-borne blend of natural plant oils and other special ingredients to nourish and protect all types of timber. The plant oils originate from sustainable sources and are used largely to replace crude oil derived components used in synthetic resins. It is a penetrating oil drying to a hard, durable and water resistant seal. It adds warmth and depth to all woods and does not leave a surface film to scratch or chip. The product conforms to The Articles in Contact with Food Regulations and is therefore suitable for use in contact with food.

The surface must be clean, bare and sanded smooth. Bare wood may be dyed if required with Rustins Wood Dye. If a natural open grain is not required such as with oak, then use Rustins Grain Filler prior to oiling.

Do not dilute product. Using a clean soft cloth or brush apply a liberal coat of Worktop Oil, working with the grain. Wipe off any excess within 3-5 minutes. New or bare wood needs to be oiled 3 times initially. Some wood may need a light sanding between coats.

The Worktop Oil is touch dry within 1 hour and can be recoated within 3 hours depending on temperature and humidity. Do not use below 10°C.

Regular maintenance is recommended to keep surfaces in good condition. When applying to previously oiled wood the surface should be first cleaned and any wax removed with white spirit or Rustins Surface Cleaner. If compatibility with previously coated surface is not known, then carry out a small coating test.

1 litre covers approximately 13 square metres per coat depending on the absorbency of the wood.

Remove as much product as possible from brushes before cleaning. Clean brushes whilst wet with water and detergent. Hard brushes can be cleaned with Rustins Brush Restorer.

Rags used for oiling must be laid out flat to dry or destroyed, otherwise they may catch fire due to spontaneous combustion.

Some local authorities have special facilities for disposal of waste paints/varnishes/coatings. Do not empty product into drains or watercourses.

Store in a cool dry place with lid tightly closed. Protect from frost.

HEALTH AND SAFETY:

Causes skin irritation. Causes serious eye irritation. Wash hands, forearms and face thoroughly after handling. Wear protective gloves/protective clothing/ eye protection/face protection/hearing protection. IF ON SKIN: Wash with plenty of water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Contains Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

UFI: RC5A-7FLL-SW00-BEDT

Please refer to Product Data Sheet for full information
at www.rustins.co.uk



EU Limit value for this product (CAT A/h):
30g/l (2010).
This product contains
max 3g/l VOC.

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom rustins@rustins.co.uk
Telephone: +44 (0)20 8450 4666
R01: Excellence Ltd, 43 Grange Parade,
Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



Walnut worktops have immense character, fantastic grain patterns and colour variation



Cherry is a warm timber with reddish hues that will darken over time to a beautiful dark reddish brown.



Beech has a sleek, consistent finish. The light tone and soft grain creates a bright feel that will complement any kitchen.



Maple is a classic European hardwood which over time matures with beautiful honey hues.



Natural Oak has a rustic finish with lots of character. It is extremely hard wearing and durable.



Quick Dry

Worktop Oil

Easy wipe-on Natural finish



- Food Safe
- Solvent Free
- Hygienic
- Water Based
- Natural Ingredients
- Quick Drying
- Low Odour



500mle

FOR INTERIOR USE ON ALL SOLID WOOD WORKTOPS