

EVERBUILD ALL PURPOSE POWDER FILLER



Colour	Product Code	Pack Size	Box Qty
White	FILL15	1.5KG	10
	FILL450	450GRM	16
	FILL9	9KG	1

Product Description

ALL PURPOSE POWDER FILLER is a high strength powder filler which is the ideal choice for most indoor repairs. When mixed with water, the filler is ready to apply in one minute and dries in about one hour to a smooth sandable finish. Due to the high levels of added PVA powder, this filler will not shrink or crack and is strong enough to accept nails and screws.

Benefits

- Heavy-duty tough filler – will accept nails or screws when dry.
- Non Shrink.
- Overpaintable with most solvent based and emulsion paints.
- Overstainable.

Areas For Use

- Indoor/outdoor repairs to plaster, plasterboard, brick, render, wood, stone and most other building materials. NOTE; Exterior use; always overpaint with oil based primer and top coat to protect filler.

Limitations

- Do not use to fill plastic or metals.
- For holes deeper than 1½ inch, apply in layers and allow to dry before applying second layer.
- Do not add further water once the filler has started to go off. Remix a fresh batch.
- Allow to fully dry before overcoating.
- Not recommended for overhead repairs. Use ONE STRIKE lightweight filler.
- As the manufacturer cannot know all the uses its products may be put to, it is the users responsibility to determine suitability for use. If in doubt, contact technical Services Dept for advice.

Surface Preparation

All surfaces must be clean, dry and free from dust, grease and other contamination. Provide a key to gloss painted surfaces. Cover nail or screw heads with oil based paint and allow to dry. Dampen all porous surfaces to improve adhesion.

Application

Always use a clean mixing vessel and add 2 parts powder to one part cold water and immediately mix to a smooth paste. The mixed filler will remain workable for 30-40 minutes. Press the filler into the repair with a spreader or filling knife. Fill the hole proud to allow for sanding and finish with a wet knife. Once dry, sand to a smooth finish. The filler may be papered over, painted or stained when dry.

Cleaning: All tools should be cleaned immediately after use with warm water.

Specific Data

Appearance	White / Off White Powder
S.G. at 20°C	2.0gcm ³ (approx)
Movement Accommodation	Low – Dries hard
Maximum Fill	40mm in one coat -further layers may be built up
Maximum Width	50mm
Application Temperature	5°C to 30°C.
Drying Time	1-8 hours depending on depth and temperature
pH	8.5-9.5 when mixed.
Solids Content	100% w/w (powder)

Health & Safety

Consult MSDS for full list of hazards.

Storage

Store in cool, dry conditions. PROTECT FROM MOISTURE.

Shelf Life

24 months when stored according to manufacturers instructions, in unopened containers.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.