



Kirk Sandall Industrial Estate, Doncaster, South  
Yorkshire, DN3 1QR

+44 (0)1302 310 113  
enquiries@prosolveproducts.com  
www. prosolveproducts.com

ProSolve is trademark of S.T.L Trading Company  
Limited  
Reg in England No: 5230722  
VAT Reg No: 381 3533 58

## TECHNICAL DATA SHEET

ProSolve Bitumen Cold Joint Sealer (BITS7)

### DESCRIPTION

An applied cold joint sealer for easy sealing around vertical joints. Vital to the performance of your work, edge sealing is a mandatory requirement for the Reinstatement of the Opening of Highways. Ideal for use when carrying out road pothole repair as it creates a solid adhesive bond between the concrete and asphalt surfaces.

### PRODUCT FEATURES

- Weather-Resistant
- Instantly Waterproofs
- Clean, Efficient & Economical
- Quick and easy to apply

### PRODUCT USES

- As a tack layer before applying a tarmacadam or similar filler
- To seal vertical edges of a reinstatement
- Waterproofing the vertical edges of a reinstatement
- Sealing horizontal joints of a reinstatement

### CHARACTERISTICS

**Colour:** Black

**Form:** Liquid

**Packaging:** 750ml Aerosol

**Shelf Life:** 36 months from the date of manufacture

**Storage:** Store upright in cool dry conditions between + 5°C and 25°C. Storage outside these parameters will significantly reduce shelf life.

## **DIRECTIONS**

- Shake can well (for at least 1 minute after the ball starts to rattle)
- Invert can and spray inside edge of excavation and base ensuring complete coverage before replacing first layer of tarmacadam
- After compacting, respray edge of excavation well before placing and compacting next or final layer
- Spray over joints once repaired to further help seal and prevent water ingress

## **IMPORTANT NOTICE**

**All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, other than for fraudulent misrepresentation, ProSolve expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.**

**BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT.**