

### PRODUCT DATA SHEET

<b>Product</b>	<b>Quick Dry Small Job Gloss Paint</b>
<b>Type</b>	A gloss acrylic emulsion based paint. The finish produced is tough, durable and resistant to oil and water.
<b>Intended Use</b>	A decorative coating for application over <b>Rustins Quick Drying Primer Undercoat</b> or over existing paints and varnishes on wood and metal. For interior and exterior use.
<b>Special Features</b>	A gloss finish available in 7 attractive shades : Poppy (Red), Buttercup, Oxford Blue, Buckingham Green, Chocolate, Black & White <b>Conforms to the Toy Safety Regulations BS EN 71 Part 3 1995.</b>
<b>Preparation</b>	The surface must be clean, smooth, sound, dry and free from wax, dust and contaminants. If the wood or metal surface is bare, apply the appropriate primer and undercoat before painting. On metal use <b>Rustin's Red Oxide Metal Primer</b> . On wood use <b>Rustin's Quick Drying Primer &amp; Undercoat</b> . Prior to painting, existing coated surfaces should be cleaned with <b>Rustin's Surface Cleaner</b> , or <b>Rustins Sugar Soap</b> and sanded lightly to provide a key, prior to painting. Cracks may be filled with <b>Rustin's Wood filler</b> . Undercoat may be applied if required.
<b>Application</b>	Apply light, even coats using a good quality brush for water-based coatingd.
<b>Coats</b>	1 coat is sufficient but a second coat may be applied if required. It is better to apply two light coats rather than one heavy coat.
<b>Drying Time</b>	Touch dry within 30 minutes, depending on the temperature and humidity.
<b>Re-coating Time</b>	3-4 hours, depending on the temperature and humidity.
<b>Application Temp.</b>	Ideally, 15-25°C. Do not use below 10°C or in conditions of high humidity.
<b>Coverage</b>	12-15 sq.metres per litre depending on the absorbency of the surface.
<b>Maintenance</b>	The surface may be cleaned with a mild detergent solution or White Spirit as necessary. Worn areas may be re-coated once cleaned and lightly sanded to provide a key.
<b>Compatibility</b>	Compatible over most types of undercoat. Can be applied over top coats once thoroughly cleaned and lightly sanded to provide a key.
<b>Settlement</b>	<b>STIR WELL BEFORE USE</b>
<b>Shelf-life/Storage</b>	Many years if stored in original, tightly closed container in cool dry conditions.
<b>Hazards</b>	Keep out of reach of children. Avoid contact with skin and eyes. After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. . A full Safety Data Sheet is available upon request or on <a href="http://www.rustins.co.uk">www.rustins.co.uk</a>
<b>Clean-Up</b>	Remove excess product from brushes before cleaning. Clean brushes whilst wet with water. Hard brushes can be cleaned with <b>Rustins Brush Restorer</b> .
<b>Sizes</b>	